

SAFETY DATA SHEET

FT 200

Section 1. Identif	ication
GHS product identifier	: FT 200
Product code	: 53-G 173 (500 ml), 53-G 177 (20L), 53-G 178 (208L), 53-G 179 (1000L)
SDS no.	: L-128E
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	: Quick evaporating surface cleaner.
Manufacturer	: Walter Surface Technologies Inc. Bio-Circle – A Division of Walter Surface Technologies Inc. 5977 Trans Canada Highway Pointe-Claire, QC H9R 1C1 Canada info@walter.com www.walter.com General Information: 1-888-592-5837
Emergency telephone number (with hours of operation)	: INFOTRAC [®] 1-800-535-5053. International call collect: 1-352-323-3500 24 hours/day, 7 days/week.
Section 2. Hazard	Is identification
OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements <u>Precautionary statements</u>	: H226 - Flammable liquid and vapor.
Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P233 - Keep container tightly closed.
Response	 P303 - Reep container lightly closed. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



Storage	: P403 - Store in a well-ventilated place. P235 - Keep cool.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Product code

: 53-G 173 (500 ml), 53-G 177 (20L), 53-G 178 (208L), 53-G 179 (1000L)

Ingredient name	%	CAS number	
Isopropyl Alcohol	5 - 10	67-63-0	

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately.
Skin contact	:	Flush contaminated skin with plenty of water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Most important symptoms/effects, acute and delayed Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation

- : No known significant effects or critical hazards.
- Skin contact : No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.

Section 4. First aid measures

Over-exposure signs/symp	i <u>toms</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Notes to physician	 dical attention and special treatment needed, if necessary Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may
Totection of mat-diders	be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet or water-based fire extinguishers.
Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	



Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
	and sewers. Inform the relevant authorities if the product has caused environmental
	pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.



Section 8. Exposure controls/personal protection

Control parameters

United States

Occupational exposure limits

Ingredient name	Exposure limits
Isopropyl Alcohol	ACGIH TLV (United States, 3/2017). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. NIOSH REL (United States, 10/2016). TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. OSHA PEL (United States, 6/2016). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours.

<u>Canada</u>

Occupational exposure limits

Ingredient name	Exposure limits
Isopropyl Alcohol	CA Alberta Provincial (Canada, 4/2009).15 min OEL: 984 mg/m³ 15 minutes.8 hrs OEL: 200 ppm 8 hours.15 min OEL: 400 ppm 15 minutes.8 hrs OEL: 492 mg/m³ 8 hours.CA British Columbia Provincial (Canada, 7/2016).TWA: 200 ppm 8 hours.STEL: 400 ppm 15 minutes.CA Ontario Provincial (Canada, 7/2015).TWA: 200 ppm 8 hours.STEL: 400 ppm 15 minutes.CA Quebec Provincial (Canada, 7/2015).TWA: 200 ppm 8 hours.STEL: 400 ppm 15 minutes.CA Quebec Provincial (Canada, 1/2014).TWAEV: 400 ppm 8 hours.STEV: 500 ppm 15 minutes.STEV: 1230 mg/m³ 15 minutes.CA Saskatchewan Provincial (Canada, 7/2013).STEL: 400 ppm 15 minutes.TWA: 200 ppm 8 hours.

Appropriate engineering controls	:	No personal respiratory protective equipment normally required. Avoid breathing dust/ fume/gas/mist/vapors/spray. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
Individual protection measure	ures	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Ckin protection		



Section 8. Exposure controls/personal protection

•	• •
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a NIOSH/MSHA approved respirator if there is a risk of exposure at levels exceeding the exposure limits. Advice should be sought from respiratory protection specialists.

Section 9. Physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	1	Clear.
Odor	1	Faint.
Odor threshold	1	Not available.
рН	1	9.41 [Conc. (% w/w): 1%]
Melting point	1	-7°C (19.4°F)
Boiling point	1	94°C (201.2°F)
Flash point	1	Closed cup: 40°C (104°F)
Evaporation rate	1	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	:	Not available.
Vapor density	1	Not available.
Relative density	1	0.99 to 1.05 g/ml @ 20°C (68°F)
Solubility	1	Soluble in the following materials: cold water and hot water.
Partition coefficient: n- octanol/water	1	Not available.
Auto-ignition temperature	1	>399°C (>750.2°F)
Decomposition temperature	1	Not available.
Viscosity	1	Not available.
Flow time (ISO 2431)	1	Not available.
VOC content	1	7.1% (w/w)



Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials and acids.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

A	С	u	t	e	1	C	X	đ	С	itv	V
-	-	-		-	-	-	-		-	-	

Product/ingredient name	Result	Species	Dose	Exposure
Isopropyl Alcohol	LD50 Dermal LD50 Oral		12800 mg/kg 5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
	Eyes - Moderate irritant Eyes - Moderate irritant Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit Rabbit Rabbit	-	24 hours 100 mg 10 mg 100 mg 500 mg	- - -

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
Isopropyl Alcohol	-	3	-

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

Name	Category	Target organs
Isopropyl Alcohol	Category 3	Narcotic effects

Specific target organ toxicity (repeated exposure)

There is no data available.

Section 11. Toxicological information

Aspiration hazard

Ingestion

There is no data available.

Information on the likely routes of exposure	: Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the physical sectors and the sectors are sectors and the sectors are sectors a	ical, chemical and toxicological characteristics
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

: No known significant effects or critical hazards.

to and also enrolle encots nom short and long ter
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
ects
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates	
Route	ATE value
Oral	35577 mg/kg



Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	Acute LC50 1400000 µg/L Marine water	· · · · · · · · · · · · · · · · · · ·	48 hours 48 hours 96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
FT 200	-	>95%; 28 to 100 day(s)	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Isopropyl Alcohol	0.05	-	low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.





Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	UN1993	UN1993	UN1993	UN1993
UN proper shipping name	FLAMMABLE LIQUIDS, N.O.S. (Isopropyl Alcohol)	FLAMMABLE LIQUIDS, N.O.S. (Isopropyl Alcohol)	FLAMMABLE LIQUIDS, N.O.S. (Isopropyl Alcohol)	FLAMMABLE LIQUIDS, N.O.S (Isopropyl Alcohol)
Transport hazard class(es)	3	3	3	3
Packing group	111	111	111	111
Environmental hazards	No.	No.	No.	No.
		•		ERG : 128

Additional informationDOT Classification: This product may be re-classified as "Combustible Liquid," unless transported by vessel
or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are
not regulated as hazardous materials.TDG Classification: Product classified as per the following sections of the Transportation of Dangerous
Goods Regulations: 2.18-2.19 (Class 3).Special precautions for user: Transport within user's premises: always transport in closed containers that are
upright and secure. Ensure that persons transporting the product know what to do in
the event of an accident or spillage. Protect from freezing. Freezing will damage product
and render it unusable.

Section 15. Regulatory information

U.S. Federal regulations	: United States inventory (TSCA 8b): All components are listed or exempted.
	Clean Water Act (CWA) 307: Benzene; Toluene; Ethylbenzene
	Clean Water Act (CWA) 311 : Propylene oxide; Potassium hydroxide; Benzene; Toluene; Ethylbenzene; Ammonia, anhydrous
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
<u>SARA 302/304</u>	
Composition/information of	on ingredients





Section 15. Regulatory information

		SARA 302 TPQ SARA 304 RQ		04 RQ	
Name	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ammonia, anhydrous	Yes.	500	-	100	-
Ethylene oxide	Yes.	1000	-	10	-
Propylene oxide	Yes.	10000	1444.3	100	14.4

SARA 304 RQ

: 101517.7 lbs / 46089 kg [11936.7 gal / 45185.3 L]

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3

Composition/information on ingredients

Name	Classification
Isopropyl Alcohol	FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

SARA 313

There is no data available.

<u>State</u>	regu	lations	

Massachusetts	: The following components are listed: Isopropyl Alcohol
New York	: None of the components are listed.
New Jersey	: The following components are listed: Isopropyl Alcohol
Pennsylvania	: The following components are listed: Isopropyl Alcohol

California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Ethylene oxide, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Ethylbenzene, Cumene, 1,4-Dioxane, Propylene oxide, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

<u>Canada</u>

NDSL)

Canadian lists

- Canadian NPRI **CEPA Toxic substances**
 - : The following components are listed: Isopropyl Alcohol
- Canada inventory (DSL
- : None of the components are listed.
 - : All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data

History

Date of issue mm/dd/yyyy	: 09/30/2018
Date of previous issue	: 11/30/2015
Version	: 2
Prepared by	: KMK Regulatory Services Inc.





Section 16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.