

SAFETY DATA SHEET

POWER CLEANER 100

Section 1. Identification

GHS product identifier : POWER CLEANER 100

Product code : 53-G 253 (500 mL), 53-G 255 (3.78 L), 53-G257 (20 L), 53-G 258 (208 L)

SDS no. : L-23E
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Acidic rust and mineral deposit remover plus brightener.

Manufacturer : Walter Surface Technologies Inc.

Bio-Circle - A Division of Walter Surface Technologies Inc.

5977 Trans Canada Highway Pointe-Claire, QC H9R 1C1

Canada

info@walter.com www.walter.com

General Information: 1-888-592-5837

Emergency telephone number (with hours of

operation)

: INFOTRAC® 1-800-535-5053. International call collect: 1-352-323-3500

24 hours/day, 7 days/week.

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

AQUATIC HAZARD (ACUTE) - Category 3

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H314 - Causes severe skin burns and eye damage.

H402 - Harmful to aquatic life.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.

P273 - Avoid release to the environment. P264 - Wash hands thoroughly after handling.



Section 2. Hazards identification

Response

: P304 + P340 + P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician.

P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician.

P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage

: P405 - Store locked up.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise

: None known.

classified

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Product code

: 53-G 253 (500 mL), 53-G 255 (3.78 L), 53-G257 (20 L), 53-G 258 (208 L)

Ingredient name	%	CAS number
Phosphoric acid	5 - 10	7664-38-2
2-Butoxyethanol	1 - 5	111-76-2
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts	1 - 5	68411-30-3
Alcohols, C12-14, ethoxylated	0.1 - 1	68439-50-9

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.



Section 4. First aid measures

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes severe burns.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation No known significant effects or critical hazards.

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.





Section 5. Fire-fighting measures

Hazardous thermal decomposition products Decomposition products may include the following materials: carbon dioxide carbon monoxide phosphorus oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.





Section 7. Handling and storage

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

United States

Occupational exposure limits

Ingredient name	Exposure limits
Phosphoric acid	ACGIH TLV (United States, 3/2017).
	TWA: 1 mg/m³ 8 hours.
	STEL: 3 mg/m³ 15 minutes.
	NIOSH REL (United States, 10/2016).
	TWA: 1 mg/m³ 10 hours.
	STEL: 3 mg/m³ 15 minutes.
	OSHA PEL (United States, 6/2016).
	TWA: 1 mg/m³ 8 hours.
2-Butoxyethanol	ACGIH TLV (United States, 3/2017).
	TWA: 20 ppm 8 hours.
	NIOSH REL (United States, 10/2016). Absorbed through skin.
	TWA: 5 ppm 10 hours.
	TWA: 24 mg/m³ 10 hours.
	OSHA PEL (United States, 6/2016). Absorbed through skin.
	TWA: 50 ppm 8 hours.
	TWA: 240 mg/m³ 8 hours.
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts	None.
Alcohols, C12-14, ethoxylated	None.



Section 8. Exposure controls/personal protection

Canada

Occupational exposure limits

Ingredient name	Exposure limits
Phosphoric acid	CA Alberta Provincial (Canada, 4/2009). 15 min OEL: 3 mg/m³ 15 minutes. 8 hrs OEL: 1 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 1 mg/m³ 8 hours. STEL: 3 mg/m³ 15 minutes. CA Ontario Provincial (Canada, 7/2015). TWA: 1 mg/m³ 8 hours. STEL: 3 mg/m³ 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 1 mg/m³ 8 hours. STEV: 3 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 3 mg/m³ 15 minutes. TWA: 1 mg/m³ 8 hours.
2-Butoxyethanol	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 97 mg/m³ 8 hours. 8 hrs OEL: 20 ppm 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 20 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 20 ppm 8 hours. TWAEV: 97 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 30 ppm 15 minutes. TWA: 20 ppm 8 hours.

Appropriate engineering controls

: No personal respiratory protective equipment normally required. Avoid breathing dust/fume/gas/mist/vapors/spray. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommended: Nitrile gloves 0.4 mm thick, permeation time 480 minutes.



Section 8. Exposure controls/personal protection

Body protection : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Use a NIOSH/MSHA approved respirator if there is a risk of exposure at levels Respiratory protection

exceeding the exposure limits. Advice should be sought from respiratory protection

specialists.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. Color Yellow. Odor : Odorless. : Not available. **Odor threshold**

pН

Melting point : 0°C (32°F) : 98°C (208.4°F) **Boiling point** Flash point : Not available. : Not available. **Evaporation rate** Flammability (solid, gas) Not available. Lower and upper explosive : Not available.

(flammable) limits

: Not available. Vapor pressure Vapor density : Not available.

Relative density : 1.15 g/ml @ 20°C (68°F)

Solubility : Soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available. : Not available. **Decomposition temperature Viscosity** : Not available. Flow time (ISO 2431) : Not available. **VOC** content : 2.5 % (w/w)

Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.





Section 10. Stability and reactivity

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials and alkalis.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Butoxyethanol Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts	LD50 Oral LD50 Oral		917 mg/kg 404 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Benzenesulfonic acid, C10-13-alkyl	Skin - Moderate irritant	Rabbit	-	0.5 ml	-
derivs., sodium salts					

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
2-Butoxyethanol	-	3	-

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

There is no data available.

Information on the likely routes of exposure

: Dermal contact. Ingestion.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes severe burns.

Ingestion: No known significant effects or critical hazards.





Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No known significant effects or critical hazards.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	12702.7 mg/kg
Dermal	44000 mg/kg
	440 mg/L

Section 12. Ecological information

Toxicity

sult	Species	Exposure
te LC50 800000 µg/L Marine water te LC50 1250000 µg/L Marine water te LC50 5 mg/L Fresh water	Crustaceans - Crangon crangon Fish - Menidia beryllina Fish - Oncorhynchus mykiss - Juvenile	48 hours 48 hours 96 hours 96 hours
te te te	EC50 >1000 mg/L Fresh water LC50 800000 μg/L Marine water LC50 1250000 μg/L Marine water LC50 5 mg/L Fresh water	EC50 >1000 mg/L Fresh water LC50 800000 μg/L Marine water LC50 1250000 μg/L Marine water

Persistence and degradability





Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
POWER CLEANER 100	-	>85%; 28 to 100 day(s)	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts	0.81 3.32	-	low low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN3264	UN3264	UN3264	UN3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid)			
Transport hazard class(es)	8 CONTRACTOR 100 100 100 100 100 100 100 100 100 10	8	8	8
Packing group	III	Ш	III	Ш
Environmental hazards	No.	No.	No.	No.

AERG : 154

Additional information

TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8).





Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. Protect from freezing. Freezing will damage product and render it unusable.

Section 15. Regulatory information

U.S. Federal regulations

: United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: Benzene; Toluene; Ethylbenzene

Clean Water Act (CWA) 311: Formaldehyde; Phosphoric acid; Benzene; Toluene;

Ethylbenzene

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

		SARA 302 TPQ		SARA 304 RQ	
Name	EHS	(lbs)	(gallons)	(lbs)	(gallons)
1	Yes. Yes.	1000 500	-	10 100	-

SARA 304 RQ : 26455026.5 lbs / 12010582 kg [2759008.8 gal / 10443984.4 L]

SARA 311/312

Classification : SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Composition/information on ingredients

Name	Classification
Phosphoric acid	SKIN CORROSION/IRRITATION - Category 1B
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
2-Butoxyethanol	FLAMMABLE LIQUIDS - Category 4
	ACUTE TOXICITY (oral) - Category 4
	ACUTE TOXICITY (dermal) - Category 4
	ACUTE TOXICITY (inhalation) - Category 4
	SKIN CORROSION/IRRITATION - Category 2
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts	ACUTE TOXICITY (oral) - Category 4
·	SKIN CORROSION/IRRITATION - Category 2
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SARA 313





Section 15. Regulatory information

	Product name	CAS number
Form R - Reporting requirements	2-Butoxyethanol	111-76-2
Supplier notification	2-Butoxyethanol	111-76-2

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: 2-Butoxyethanol; Phosphoric acid

New York The following components are listed: Phosphoric acid

New Jersey : The following components are listed: 2-Butoxyethanol; Phosphoric acid : The following components are listed: 2-Butoxyethanol; Phosphoric acid **Pennsylvania**

California Prop. 65

MARNING: This product can expose you to chemicals including Benzene, Ethylene oxide, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Ethylbenzene, Cumene, Formaldehyde, 1,4-Dioxane, 2,2'-Iminodiethanol, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Canada

Canadian lists

Canadian NPRI : The following components are listed: Phosphoric acid; 2-Butoxyethanol

CEPA Toxic substances

: The following components are listed: 2-Butoxyethanol

Canada inventory (DSL

NDSL)

: All components are listed or exempted.

International lists

National inventory

Australia : All components are listed or exempted. China : All components are listed or exempted. **Europe** : All components are listed or exempted. **New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. **Taiwan** : All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method Calculation method
AQUATIC HAZARD (ACUTE) - Category 3	Calculation method

History

Date of issue mm/dd/yyyy : 09/30/2018 Date of previous issue : 04/30/2018

Version 3.1

Prepared by : KMK Regulatory Services Inc.





Section 16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

