



### Deoxidized Copper Welding Wire

- Recommended for welding applications where joints of high copper content are involved
- Deoxidized copper contains phosphorus and silicon as de-oxidizing agents which promote sound weld joints
- Produces trouble-free welds that are a good colour match to copper and have good electrical conductivity
- Can be used with inert gas arc and oxyacetylene welding
- Each container has an identification label showing grade, size, weight and heat number
- AWS A5.7, ErCu



Priced per Spool

Model No.	Mfg. No.	Dia. "	Wt. lbs.	Price/Each
TTU812	DOC035X30SP	0.035	30	
TTU813	DOC045X30SP	0.045	30	
TTU814	DOC116X30SP	1/16	30	
TTU815	DOC332X30SP	3/32	30	

#### 36" CUT LENGTH Priced per Tube

Model No.	Mfg. No.	Dia. "	Wt. lbs.	Price/Each
TTU827	DOC116X36T	1/16	10	
TTU828	DOC332X36T	3/32	10	
TTU829	DOC18X36T	1/8	10	
TTU830	DOC316X36T	3/16	10	

### Silicon Bronze Welding Wire

- Used for inert gas arc welding of copper, copper-silicon, and copper-based metals to themselves as well as to steel
- Frequently used to gas tungsten arc and gas metal arc weld coated steels
- Also used to surface areas subject to corrosion
- Each container has an identification label showing grade, size, weight and heat number
- AWS A5.27, ERCuSi-A
- Conformance certifications can be furnished upon request



Priced per Spool

Model No.	Mfg. No.	Dia. "	Wt. lbs.	Price/Each
TTU824	SIB030X2SP	0.030	2	
TTU825	SIB035X2SP	0.035	2	
TTU826	SIB045X2SP	0.045	2	
TTU820	SIB025X10SP	0.025	10	
TTU821	SIB030X10SP	0.030	10	
TTU822	SIB035X10SP	0.035	10	
TTU823	SIB045X10SP	0.045	10	
TTU816	SIB030X30SP	0.030	30	
TTU817	SIB035X30SP	0.035	30	
TTU818	SIB045X30SP	0.045	30	
TTU819	SIB116X30SP	1/16	30	

#### 36" CUT LENGTH Priced per Tube

Model No.	Mfg. No.	Dia. "	Wt. lbs.	Price/Each
TTU831	SIB035X36T	0.035	10	
TTU832	SIB045X36T	0.045	10	
TTU833	SIB116X36T	1/16	10	
TTU834	SIB332X36T	3/32	10	
TTU835	SIB18X36T	1/8	10	
TTU836	SIB532X36T	5/32	10	
TTU837	SIB316X36T	3/16	10	
TTU838	SIB14X36T	1/4	10	

### 36" Bare Nickel Silver Cut Length TIG Rods

- Recommended for applications requiring higher mechanical properties and situations where good colour match is important
- Primarily intended for braze welding steel and cast iron
- Melting point of 1680°F (916°C)
- RBCuZn-D
- **Priced per 10-lb. tube**




Priced per Tube

Model No.	Mfg. No.	Dia. "	Wt. lbs.	Price/Each
TTU851	NS116X36T	1/16	10	
TTU852	NS332X36T	3/32	10	
TTU853	NS18X36T	1/8	10	
TTU854	NS316X36T	3/16	10	
TTU855	NS14X36T	1/4	10	

### 36" Low Fuming Bronze Cut Length TIG Rods



- Fuming qualities and good mechanical properties makes it a widely used general purpose rod
- Provides higher mechanical properties than obtainable with naval bronze
- Used extensively for braze welding steel and cast iron
- Melting point of 1620°F (882°C)
- RBCuZn-C
- **Priced per 10-lb. tube**



Priced per Tube

Model No.	Mfg. No.	Description	Dia. "	Wt. lbs.	Price/Each
TTU839	LFB116X36T	Bare	1/16	10	
TTU840	LFB332X36T	Bare	3/32	10	
TTU841	LFB18X36T	Bare	1/8	10	
TTU842	LFB532X36T	Bare	5/32	10	
TTU843	LFB316X36T	Bare	3/16	10	
TTU844	LFB14X36T	Bare	1/4	10	
TTU845	LFB516X36T	Bare	5/16	10	
TTU846	LFB38X36T	Bare	3/8	10	
TTU847	LFBC332X36T	Flux-Coated	3/32	10	
TTU848	LFBC18X36T	Flux-Coated	1/8	10	
TTU849	LFBC532X36T	Flux-Coated	5/32	10	
TTU850	LFBC316X36T	Flux-Coated	3/16	10	

### 4043 & 5356 Aluminum Welding Wire

- Cleanliness, density and temper of wires are precisely controlled
- Each container has an identification label showing grade, size, weight and heat number
- Conform to AWS A5.10 classification, CWB and ABS approvals



#### 4043

- 5% silicon all position aluminum weld wire used to weld heat treatable alloys such as the 6XXX base metals and cast alloys
- Found in many common welding applications such as bicycles, trucks, trailers and automotive parts and equipment
- Silicon with these alloys give improved wetting action yielding a less crack sensitive bright weld bead



#### 5356

- 5% magnesium all position non-heat treatable wire used to weld the 5XXX series alloys
- Common welding applications such as boats, ships, bicycles, trucks, pressure vessels and automotive parts and equipment

Priced per Spool

Model No.	Mfg. No.	Dia. "	Wt. lbs.	Price/Each
TTU956	40430301SP	0.030	1	
TTU957	40430351SP	0.035	1	
TTU958	40433641SP	3/64	1	
TTU959	40430305SP	0.030	5	
TTU960	40430355SP	0.035	5	
TTU961	404303016SP	0.030	16	
TTU962	404303516SP	0.035	16	
TTU963	404336416SP	3/64	16	
TTU964	404311616SP	1/16	16	

#### 5356

- |        |             |       |    |  |
|--------|-------------|-------|----|--|
| TTU965 | 53560301SP  | 0.030 | 1  |  |
| TTU966 | 53560351SP  | 0.035 | 1  |  |
| TTU967 | 53563641SP  | 3/64  | 1  |  |
| TTU968 | 53560305SP  | 0.030 | 5  |  |
| TTU969 | 53560355SP  | 0.035 | 5  |  |
| TTV020 | 53563645SP  | 3/64  | 5  |  |
| TTU970 | 535603016SP | 0.030 | 16 |  |
| TTU971 | 535603516SP | 0.035 | 16 |  |
| TTU972 | 535636416SP | 3/64  | 16 |  |
| TTU973 | 535611616SP | 1/16  | 16 |  |

#### 36" CUT LENGTH Priced per Package

Model No.	Mfg. No.	Dia. "	Wt. lbs.	Price/Each
TTU974	404311636T	1/16	10	
TTU975	404333236T	3/32	10	
TTU976	40431836T	1/8	10	
TTU977	404353236T	5/32	10	
TTU978	404331636T	3/16	10	

#### 5356

TTU979	535611636T	1/16	10	
TTU980	535633236T	3/32	10	
TTU981	53561836T	1/8	10	
TTU982	535653236T	5/32	10	
TTU983	535631636T	3/16	10	